



	MWP-3			
Screen Dimension(inch)	90	80	70	55
Display Dimension(mm) (WxH)	2000 x 1172	1750 x 1000	1000 x 1469	750 x 1172
Resolution (dot) (WxH)	512 x 300	448 x 256	256 x 376	192 x 300
Profile Dimension (mm)(WxH)	2016 x 1292 x 78	1766 x 1117 x 78	1016 x 1592 x 78	766 x 1291.5 x 78
LED Specification	2121			
Pixel Pitch (mm)(horizontal/ vertical)	3.91-3.91			
Pixel Density (dot/m²)	65536			
Transparency Rate	92%			
Brightness(cd/m²)	≥3000 (Black Light) ; ≥4500(White Light)			
Maximum Power Consumption (w/m²)	865			
Average Power Consumption (w/m²)	330			
Color Temperature(K)	3000 - 10000			
Scanning Mode	Static Driving (Single Pixel Single Control)			
Frame Rate (Hz)	60 - 120			
Encapsulation Type	Light Board & Driving Board Integrated			
Lifespan	≥ 100,000.00 hours			
Pixel Configuration	16bit			
Input Voltage	AC100 - 240V 50/60Hz			
Working Voltage for Module	DC4.2V ±0.2V			
Working Temperature	Temperature -20°C - 50°C			
Working Humidity	Humidity 20%RH - 85%RH (Without Condensation)			
Storage Temperature	Temperature -20°C - 60°C			
Storage Humidity	Humidity 10%RH - 85%RH (Without Condensation)			
Protection Degree	IP20			
Installation Method	Hanging Up			
Installation Environment	Indoor			
Packing Way	Pearl Cotton+Carton/Flight Case			





## About TIVA

